




Golden Supreme

15W40 CI-4

NFPA 704



SAFETY DATA SHEET (SDS)

1. IDENTIFICATION OF THE PRODUCT AND COMPANY

Name: 15W40 Motor Oil

Producer: Olein Recovery Corp

Chemical Name: Petroleum Hydrocarbon

Commercial Name: Golden Supreme 15W40 CI-4 API SN

Emergency Tel.: + 1 800 542 7209
+ 1 787 266 2103

Fax:+1 787 893 0224

Address:

Carretera 901 Km. 2.7 Bo. Camino Nuevo. Yabucoa. Puerto Rico. PR 00767.

Web:www.oleinrefinery.com

2. HAZARDS IDENTIFICATION

OSHA/HCS status: The material is considered non-hazardous according to regulatory guidelines.

Substance/mixture: This product is a mixture

Classification of the substance or mixture:

Flammable Liquids; Hazard Category 4
Skin irritation / Eye irritation; Category 2 (skin) 2A (eye)
Specific Target Organs Toxicity (single exposure); Category 2
Specific target organ exposure – Skin; Category 2
Harmful if swallowed; Category 3
May be harmful to aquatic Life; Category 4.

GHS label elements

Hazard pictograms:



Signal word:

WARNING

Hazard statements:

H227	Combustible liquid – Flammable Liquids.
H315 + H320	Skin irritation / Eye irritation.
H320	Eye irritation



H371 Specific Target Organs Toxicity (single exposure)
H372 Specific target organ exposure – Skin
H302 Harmful if swallowed.

Precautionary statements:

P202 Do not handle until all precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces.
P233 Keep container tightly closed.
P260 Do not breath dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash hands and forearms thoroughly after handling.
P330 Rinse mouth.

Hazards not otherwise

Classified: None

HEALTH RISKS

Eye Contact: Causes eyes irritation.
Skin Contact: Causes skin irritation.
Inhalation: May cause respiratory irritation.
Ingestion: Can cause a laxative effect.

EFFECTS OF LONG-TERM EXPOSURE (CHRONIC):

Carcinogenesis: This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA, or ACGIH, as of this date, greater or equal to 0.1%.

Teratogenicity and Embryotoxicity: Not determined

Mutagenesis: Not determined

3. COMPOSITION / INFORMATION OF THE INGREDIENTS

Substance/mixture: This product is a mixture

<u>Components</u>	<u>CAS Registry No.</u>	<u>Concentration Percent (%)</u>
Lubricating Oils (petroleum), hydro treated spent	64742-58-1	80-85
Proprietary	Performance Additives	15-20
64742-28-1	Base Oil	>99
	Viscosity Improver	1



4. FIRST AID

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this SDS.

Inhalation:	Move exposed person to fresh air. Get medical attention if symptoms occur.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
Skin Contact:	After contact with skin, wash immediately with plenty of soap and water. Get medical attention if symptoms occur.
Notes to physician:	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Carcinogenic Potential:	This product is not known to contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC or NTP.

5. FIRE FIGHTING MEASURES

NFPA Flammability Classification:	NFPA Class-IIIB combustible material.
Autoignition Temperature:	Not determined.
Flash Point:	> 442°F (228°C)
Hazardous Combustion Products:	No specific data
Extinguishing Media:	Appropriate Extinguishing Media: Use an extinguishing agent suitable for the surrounding fire. Use foam, dry chemical or water spray (fog) to extinguish fire. Inappropriate Extinguishing Media: Straight Streams of Water. Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.



For large storage fires involving this material and/or other lubricating products, do not enter any enclosed or confined space without full protective equipment including self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products, and oxygen deficiencies.

6. MEASURES IN CASE OF AN ACCIDENTAL SPILL

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, Hazards Identification on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this SDS.

Personal Precautions:

Put on appropriate personal protective equipment (see section 8). Ventilate area if confined or poorly ventilated.

Spill Management Small Spill:

Absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill:

Prevent entry into sewers, water courses, basements or confined areas. May require pump or vacuum to get the most of the spill prior to absorbent. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Environmental Precautions Large Spills:

Dike far ahead of liquid spill for later recovery and disposal. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). May require removal of severely contaminated soil.

Waste Disposal Method:

Place contaminated material in disposable containers. Material must be disposed of in accordance with Federal, State, and Local regulations. Contact the RCRA Superfund Hotline directly @ (800) 424-9346, a regional US EPA office, or an authorized waste management facility to provide guidance concerning case specific disposal issues.



7. HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment. Avoid contact with used product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, odorous and toxic fumes may form from the decomposition of the product if stored at excessive temperatures for extended periods of time. Keep away from incompatible materials, food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatibilities: Strong oxidizing agents.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Environmental Exposure control: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Safety eyewear should be used when there is a likelihood of exposure. Not required under normal conditions of use. Recommended: Face shield or goggles.

Hand Protection: Use gloves appropriate for work or task being performed. Not required under normal conditions of use. Recommended: Impervious protective gloves of Viton or nitrile rubber

Respiratory Protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Not required under normal conditions of use. If exposure limits are exceeded use a NIOSH approved respirator. Supplied Air Respirator is recommended for entry into confined spaces or other poorly ventilated areas.

Body Protection: No special protective clothing is required under normal conditions of use. Where spills and splashes are possible, wear appropriate oil impervious protective clothing. Clean water should be available in work areas for flushing the eyes and skin.

General Comments: This is a general recommendation based upon general information as to normal uses and conditions. However when special or unusual uses or conditions exist,



it is suggested that an expert assistance of an industrial hygienist be sought for special equipment.

Occupational Exposure Guideline Exposure Limits in air (United States)

Chemical Name	OSHA PEL	ACGIH
Lubricating oils, Petroleum Hydrotreated spent	TWA: 5mg/m ³ , as oil mist, mineral	TWA: 5mg/m ³ , as oil mist, mineral STEL: 10mg/m ³ , as oil mist, mineral

11. TOXICITY INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this SDS.

Low order of acute toxicity, but aspiration following ingestion and vomiting may cause severe and potentially fatal chemical pneumonitis. Does not absorb in acute toxic amounts through the skin. Exposure to high concentrations of oil mist may cause irritation to the respiratory organ. Exposure to the eye is slightly irritating, but does not injure eye tissue. Continuous or repeated skin contact combined with poor personal hygiene may cause dermatitis like eczema and oil acne. Used oil may contain harmful contaminants.

Skin Contact: Product that under high pressure has been forced under the skin may cause serious cell damage/death under the skin.

Toxicity Data

Distillates, petroleum, solvent-refined heavy paraffinic
Oral (LD50): Acute: >5000 mg/kg [Rat].
Dermal (LD50): Acute: >2000 mg/kg [Rabbit].
Inhalation (LC50) Acute: =2.18 mg/L (Rat) 4 h

Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested. Analyses conducted by method IP 346 indicate that the concentration of DMSO extractable in this mineral oil is below 3.0 weight percent.

Residual oils, petroleum, solvent-refined:

Oral (LD50): Acute: >5000 mg/kg [Rat].
Dermal (LD50): Acute: >2000 mg/kg [Rabbit].

Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well



above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.

Carcinogenicity: No ingredients of this product, present at equal to or greater than 0.1% of the product, are listed by OSHA, NTP, or IARC as suspected carcinogens.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl. Not harmful to aquatic organisms. Expected LC/EC 50 value > 100 mg/l.

Mobility: Low solubility in water, floats on water. **Degradability:** Potentially degradable, but will persist in the environment for long periods. **Other Effects:** An oil film may cause physical damage to organisms and disturb the transportation of oxygen in the intermediate zone between air/water or water/air.

**Environmental
Fate:**

An ecological effect testing has not been conducted on this product. However, plants and animals may experience harmful or fatal effects when coated with petroleum-based products. Petroleum-based (mineral) lube oils will normally float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway might be enough to cause a fish kill or create an anaerobic environment.

13. DISPOSAL CONSIDERATIONS

Waste Disposal

Methods: Dispose in accordance with Federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

Contaminated

Packaging: Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

14. TRANSPORT INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.



US DOT	Not regulated by the U.S. Department of Transportation as a hazardous material.
Proper Shipping Name	Not regulated.
Hazard Class	Not regulated.
Packing Group(s)	Not applicable.
UN/NA Number	Not regulated.
Reportable Quantity	A Reportable Quantity (RQ) has not been established for this material.
Placard(s)	No placard necessary.
Emergency Response Guide No.	Not applicable.
MARPOL III Status	Not a DOT "Marine Pollutant" per 49 CFR 171.8.

15. REGULATORY INFORMATION

TSCA Inventory:

This product is in U.S. commerce, and listed in the TSCA Inventory of Chemicals; hence, it may be subject to applicable TSCA provisions and restrictions. SARA 302/304 Emergency Planning and Notification: The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

SARA 313 Toxic Chemical Notification and Release Reporting:

This product does not contain greater than 1.0% of any chemical substance of Section 313 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

CERCLA:

The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4 as hazardous substance.

SARA 311/312 Hazard Identification:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2.



This material would be classified under the following hazard categories:

- Acute Health Hazard: Yes
- Chronic Health Hazards: No
- Fire Hazard: No
- Sudden Release Of Pressure Hazard: No
- Reactive Hazard: No

Clean Water Act (CWA): This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

Additional Regulatory Remarks: No additional regulatory remarks.

16. OTHER INFORMATION

ABBREVIATIONS: USA: Administration (OSHA) Safety and Occupational Health (IARC) International Agency for Research on Cancer (NTP) National Toxicology Program (NFPA) National Association of Fire Protection (NIOSH) National Institute for Occupational Safety and Occupational health (ACGIH) American Conference of Governmental Industrial Hygienists.

Previous review: 01/12/14

DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER

REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

