

DIESEL OIL CF-2

ACEITE PARA MOTORES A DIESEL



DESCRIPCIÓN:

La serie GOLDEN SUPREME HEAVY DUTY es un lubricante de alta viscosidad desarrollado con bases minerales hidro fragmentadas y un paquete de aditivos de tecnología muy avanzada que nos permite exceder las necesidades de protección en motores para diesel, ya sean turbocargados o sobrealimentados, manteniendo una alta presión en el aceite.

APLICACIONES:

Particularmente recomendado para los motores diesel más recientes de vehículos pesados, autobuses, maquinaria de construcción o agricultura, con o sin turbocompresores.

VENTAJAS & BENEFICIOS:

- Poder detergente y dispersante muy elevado que evita la formación de depósitos y el pulido de los cilindros, garantizando la limpieza de los pistones.
- Excelente comportamiento a temperaturas extremas.
- Facilita el arranque, disminuyendo notablemente la fricción de las piezas vitales del motor y reduce el desgaste prematuro.
- Menor consumo de aceite, mayor protección contra el desgaste y alta presión de aceite a lo largo de un amplio rango de temperaturas de operación.

Seguridad y manejo:

Basado en la información disponible, no se espera que este producto cause efectos adversos en la salud cuando se utiliza para la aplicación prevista y las recomendaciones de la Ficha de Datos de Seguridad (FDS) se siguieron. SDS's están disponibles bajo petición. Este producto no debe utilizarse para fines distintos de su uso previsto. Al deshacerse del producto usado, tenga cuidado para proteger el medio ambiente.

DESCRIPTION:

GOLDEN SUPREME HEAVY DUTY series is a high viscosity lubricant developed with hydro-cracked mineral bases and an additive pack of the latest technology which allows us to exceed the requirements for protection of diesel engines, including turbo-charged and supercharged, by maintaining high pressure on the oil.

APPLICATIONS:

Particularly recommended for the latest diesel engines of trucks, buses, construction machinery or agriculture, with or without turbochargers.

ADVANTAGES & BENEFITS:

- *Very high detergency and dispersancy that prevents the buildup of deposits and the polishing of cylinders, ensuring piston cleanliness.*
- *Excellent performance at extreme temperatures.*
- *Easy starting, greatly reducing friction of vital engine parts and reducing premature wear.*
- *Lower oil consumption, increased wear protection and higher oil pressure over a wide range of operating temperatures.*

Safety and Handling:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.



ESPECIFICACIONES / SPECIFICATIONS

- API CF-2,CF
- Detroit Diesel Series 53,71,92

CARACTERÍSTICAS / CHARACTERISTICS:

CHARACTERISTICS	ASTM	SAE 30	SAE 40	SAE 50
Density Lb/Gal	Gardner	7.4	7.4	7.45
API Gravity	D-1298	28.3	27.3	26.8
Specific Gravity @ 15.6 °C	D-1298	0.885	0.891	0.893
Viscosity Index	D-2270	104	98	99
Viscosity 40°C, cSt	D-445	92.8	173.4	214.5
Viscosity 100°C, SUS	D-88	480	915.1	1135.6
Viscosity 100°C, cSt	D-445	11	15.7	18.19
Viscosity 210°C, SUS	D-88	63	82.8	93.4
Pour Point °C (°F)	D-97	-26 (-15)	-11 (12.2)	-10 (14)
Flash Point C.O.C. °C (°F)	D-92	218 (424)	230 (446)	256 (493)
TBN, mg/g KOH	D-2896	10	10	10

** These characteristics are typical of current production. Whilst future production will conform to specification, variations in these characteristics may occur.

PACKAGING / EMPAQUE:

GOLDEN SUPREME CF-2			Grade	SAE 30			
PACKAGING	PART #	UPC #	VOLUME	PRODUCT SIZE	CASE	CASE SIZE	PALLET QNTY
QT.	GSP-136-C	0 1889002051 0	32 OZ	9"x4¼"x2¾"	12/1QT	9½"x13¼"x10¼"	
PAIL	GSP-136-P	7 1889000104 4	5GL	14½"x12½"x12½"	1/5GL	-	
DRUM	GSP-136-D	7 1889000103 7	55GL	35½"x22¾"x22¾"	1/55GL	-	



GOLDEN SUPREME CF-2			Grade	SAE 40			
PACKAGING	PART #	UPC #	VOLUME	PRODUCT SIZE	CASE	CASE SIZE	PALLET QNTY
QT.	GSP-138-C	0 1889014229 8	32 OZ	9"x4 ¹ / ₄ "x2 ⁵ / ₈ "	12/1QT	9 ¹ / ₂ "x13 ¹ / ₄ "x10 ¹ / ₄ "	
GALLON	GSP-138-G	0 1889014230 4	128OZ	11 ¹ / ₂ "x6 ⁵ / ₈ "x4 ³ / ₈ "	4/1GL	12 ¹ / ₄ "x14 ¹ / ₄ "x9 ¹ / ₂ "	
PAIL	GSP-138-P	7 1889000108 2	5GL	14 ¹ / ₂ "x12 ¹ / ₂ "x12 ¹ / ₂ "	1/5GL	-	
DRUM	GSP-138-D	7 1889000107 5	55GL	35 ¹ / ₂ "x22 ³ / ₄ "x22 ³ / ₄ "	1/55GL	-	

GOLDEN SUPREME CF-2			Grade	SAE 50			
PACKAGING	PART #	UPC #	VOLUME	PRODUCT SIZE	CASE	CASE SIZE	PALLET QNTY
QT.	GSP-141-C	0 1889014232 8	32 OZ	9"x4 ¹ / ₄ "x2 ⁵ / ₈ "	12/1QT	9 ¹ / ₂ "x13 ¹ / ₄ "x10 ¹ / ₄ "	
GALLON	GSP-141-G	0 1889014233 5	128OZ	11 ¹ / ₂ "x6 ⁵ / ₈ "x4 ³ / ₈ "	4/1GL	12 ¹ / ₄ "x14 ¹ / ₄ "x9 ¹ / ₂ "	
PAIL	GSP-141-P	7 1889000114 3	5GL	14 ¹ / ₂ "x12 ¹ / ₂ "x12 ¹ / ₂ "	1/5GL	-	
DRUM	GSP-141-D	7 1889000113 6	55GL	35 ¹ / ₂ "x22 ³ / ₄ "x22 ³ / ₄ "	1/55GL	-	