

ATF DEXRON III

DESCRIPCIÓN:

Golden Supreme Dex III Series es un producto a base de minerales que fue diseñado originalmente para su uso en pre 2005 transmisiones automáticas instaladas en vehículos de General Motors. Debido a que tiene un alto índice de viscosidad que se especifica para muchas aplicaciones industriales y en alta mar en donde se requiere el rendimiento Dexron II o III o Mercon. No se debe utilizar cuando se requieren Dexron® VI, V o Mercon® Mercon® SP.

APLICACIONES:

Recomendado para muchas transmisiones utilizados en los automóviles de General Motors, Holden, Isuzu, Opel y Hydramatic® transmisiones utilizan en una amplia gama de vehículos. Cumple Dexron III - IH, IID y II. Adecuado como fluido de la dirección asistida. También es adecuado para muchos vehículos japoneses modelo anterior donde se recomiendan los líquidos de tipo Dexron®. Se recomienda para otras transmisiones donde se especifican los fluidos Dexron® y Dexron® II, a excepción de Mercedes -Benz, ZF, BMW, Voith y Renk.

VENTAJAS & BENEFICIOS:

- Durabilidad de fricción mejorada prolonga la vida de la transmisión y promueve cambios suaves.
- Aumento de la resistencia a la oxidación del aceite y la degradación
- Aumento de la banda de embrague y la capacidad del conjunto de embrague
- Mejora de la protección de los componentes de cobre y bronce.

Seguridad y manejo:

Basado en la información disponible, no se espera que este producto cause efectos adversos en la salud cuando se utiliza para la aplicación prevista y las recomendaciones de la Ficha de Datos de Seguridad (FDS) se siguieron. SDS's están disponibles bajo petición. Este producto no debe utilizarse para fines distintos de su uso previsto. Al deshacerse del producto usado, tenga cuidado para proteger el medio ambiente.

DESCRIPTION:

GOLDEN SUPREME Dex III Series is a mineral based product which was originally designed for use in pre 2005 automatic transmissions fitted to General Motors vehicles. Due to it having a high viscosity index it is specified for many industrial and offshore applications where Dexron II or III or Mercon performance is required. It should not be used where Dexron® VI, Mercon® V or Mercon® SP are required.

APPLICATIONS:

Recommended for many transmissions used in General Motors cars, Holden, Isuzu, Opel and Hydramatic® transmissions used in a range of vehicles. Meets Dexron III-IH, IID and II. Suitable as Power steering fluid. It is also suitable for many earlier model Japanese vehicles where Dexron® type fluids are recommended. It is recommended for other transmissions where Dexron® and Dexron® II fluids are specified except Mercedes-Benz, ZF, BMW, Voith and Renk.

ADVANTAGES & BENEFITS:

- Enhanced friction durability prolongs transmission life and promotes smooth shifting.
- Increased resistance to oil oxidation and degradation
- Increased clutch band and clutch pack capacity.
- Improved protection of copper and bronze components.

Safety and Handling:

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.



CARACTERÍSTICAS / CHARACTERISTICS:

CHARACTERISTICS	ASTM	DEX III
API Gravity @ 60 °F	D-1298	33.2
Viscosity Index	D-2270	170
Viscosity 40°C, cSt	D-445	39.2
Viscosity 100°C, cSt	D-445	7.7
Pour Point °C (°F)	D-97	-50
Flash Point C.O.C. °C (°F)	D-92	233°C (451°F)
Color	D-1500	RED
Boron, ppm	D-4951	110
Phosphorus, ppm	D-4951	30

** These characteristics are typical of current production. Whilst future production will conform to specification, variations in these characteristics may occur.

PACKAGING / EMPAQUE:

GOLDEN SUPREME ATF			Grade	DEXRON III			
PACKAGING	PART #	UPC #	VOLUME	PRODUCT SIZE	CASE	CASE SIZE	PALLET QNTY
GALLON	GSP-117-G	3 1889024452 8	128oz.	11 ½"x6 ⅝" x4 ⅜"	4/1GL	12 ¼"x14 ¼"x9 ½"	-
PAIL	GSP-117-P	7 1889000062 7	5GL	14½"x12½"x12½"	1/5GL	-	-
DRUM	GSP-117-D	7 1889000061 0	55GL	35 ½"x22 ¾"x22 ¾"	1/55GL	-	-